

SAFETY BLOW GUN



SERIES 605 1/4" NPTF inlet

- Trouble-free, unitized, die cast body
- When tip is fully obstructed, @ 150 PSI input, relieving side holes drop tip-pressure to a safe 14.5 PSI
- Complies with OSHA Section 1910, 242(b)
- Bright chrome finish
- Cushioned thumb-lever
- Convenient, integral, hanger hook

BLOW-CLEAN GUN



SERIES 610 1/4" NPTF inlet

- Rubber tip directs air jet for blow-cleaning surfaces or cavities
- Tip can't scratch or mar finished surfaces
- Body features same as Series 605, but WITHOUT safety side holes
- Should be used only with 30 PSI line pressure or less
- When rubber tip is removed, a 1/8" female pipe thread is available for attaching extension tubes and other accessories

AIR ADJUSTING VALVE (NOT A SHUT-OFF VALVE)



SERIES 1200 1/4" NPTF ports

- Permits accurate flow control in either direction
- Set knurled knob to desired flow rate
- Spring-loaded ratchet permits positive flow adjustment without drift
- Oil resistant seals prevent leakage

TOMCO GARDEN HOSE

Working Range:
Maximum Operating Pressure;
To 200 psig
Temperature: -40° to +200° F

SERIES GH

GARDEN HOSE THREAD



PLUG (Hose Stem)



PLUG



MANUAL COUPLER

Size	Catalog No.	Catalog No.	Catalog No.
5/8" Hose I.D.	GHP-10HB	-	-
3/4"-11.5NH Male Thread	-	GHP	-
3/4"-11.5NH Female Thread	-	-	GHC

Dual Seal Water Service Design:

Ideal for frequent connect/disconnect water hose applications in industrial wash systems, food preparation plants, paper, agricultural watering, etc. O-ring in coupler body seals on the plug nose. Flat washer in coupler seals on the faucet thread.