

## Pneumatic Couplings, Fittings and Accessories

Page

### Single Shut-Off Couplings

TOMCO offers a wide selection of premium quality pneumatic couplings that interchange with other popular coupler brands.

#### Basic

Size	Series	Interchange	
1/8"	SC	RECTUS 21	2
1/4"	Universal	ARO, Parker (Tru-flate), Industrial	2
1/4"	U2	ARO, Tru-flate Ind.	3
3/8"	U3	Un. Safety Coupler	3
1/4"	100 & A100	ARO 210, Industrial	4
1/4"	180, M180, A180	Industrial, MIL-C-4109	5
1/4"	2100 & A2100	Parker (Tru-flate)	6
1/4"	1100	Lincoln	7
1/4"	TL	Schrader	7
3/8"	T4000, T400 & PT 400	Industrial	8
3/8"	PT 400 & T500	Parker (Tru-flate)	9
1/2"	T500	Parker (Tru-flate)	9
1/2"	T5000, T500	MIL-C-4109	10

### Hose Fittings, Hose Splice, Male and Female Stems, and Reusable Fittings

11

### "Slim-Flow" Quick Connect, Series 3400, 3600 & 3800

34

This precision line of couplers is ideally suited for instrumentation and chemical processing applications.

### Blow Guns and Accessories

13

### Slide Valves

12

### Check Valves

12

### Safety Relief Valves, Series 1780

36

For air compressor storage tanks. ASME Coded.

### Pressure Relief Valves, Series 1776K

37

Developed for electrical distribution transformers.

## Hydraulic/Fluid Couplers, Fittings and Accessories

### Straight Through/Full Flow Couplers, Series ST

30

## Double Shut-Off Couplers

Series	Interchange	Page
PC	Pioneer	25
CD	Pioneer Interchange with Double Acting Sleeve	27
CU	Pioneer Interchange Couple Under Pressure	27
A5100	Thread-to-Connect Couple-under-pressure couplings ideally suited for mining, bulk hauling, oil field, construction or other applications where connections must be made with trapped line pressure.	22
JC	Thread-to-Connect 10,000 PSI, designed for hydraulic ram service	24
A5600	General Purpose ISO "A" Two-way coupler for mobile hydraulic equipment.	20
THK	Industrial Interchange ISO "B" Two-way coupler for general industrial hydraulic applications.	17
THK 12	High Flow 1-1/2" basic size for high volume fluid transfer applications such as return lines.	19
FE	Flush Face International Interchange Minimum spill flat face couplers ideally suited for mobile hydraulic equipment.	14
FF	Flush Face, High Pressure Similar to Series FE but with working pressure ratings up to 10,000 psi.	16
FS	Flush Face, Stainless Steel 316 stainless steel construction is ideal for highly corrosive environments.	16
DK	6,000 PSI Designed for diagnostic equipment, interchangeable with Parker PD Series.	28

## Mold Coolant-Line Quick Couplers

These brass couplings have been especially developed for quick connection and disconnection of fluid lines on plastic injection molds.

Series	Interchange	
MC200, 300 & 500	D-M-E, Parker, Foster	31

## Garden Hose Couplings, Series GH

13

Professional garden hose couplers for specialty markets

## Product Information

Safety Guide	38
Warranty, Terms and Conditions	40
Seal Material Compatibility	39
Plug Profile Selection Guide	41